Google

| naming service register object client cache | Search | Advanced Search Preferences |

Web   Results **11** - **20** of about **1,100,000** for <u>naming **service** **register** **object** **client** **cache**</u>. (0.14 seconds)

[PDF] Auto-ID **Object Name Service** (ONS) 1.0
File Format: PDF/Adobe Acrobat - View as HTML
The Auto-ID **Object Name Service** Specification 1.0 defines the working of. 134. ONS and
its interface to applications. 135. 2.1.5 ONS local **cache ...**
interval.hu-berlin.de/downloads/rfid/IT_Infrastruktur/WD-ons-1.0-20030930.pdf -
Similar pages

Title Index
[Reserved for Definitions of Managed **Objects** for the Ethernet-like Interface Types. ......
Cross **Registry** Internet **Service** Protocol (CRISP) Requirements **...**
dret.net/rfc-index/titles - 977k - Cached - Similar pages

Finding a Domain Controller in the Closest Site
The **client** stores this site **name** in the DynamicSiteName **registry** entry in
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet**Services**\ Netlogon\Parameters. ...
www.microsoft.com/technet/prodtechnol/windows2000serv/reskit/distrib/dsbc_nar_jevl.mspx
- 26k - Cached - Similar pages

[PDF] Functional Specification for **Object Caching Service** for Java ...
File Format: PDF/Adobe Acrobat - View as HTML
The **object caching service** is designed for general application use. All **objects** within the
cache are accessed. by **name**. The **name** can be any Java **object**, ...
jcp.org/aboutJava/communityprocess/jsr/**cache**FS.pdf - Similar pages

[PPT] pool.cern.ch/talks/CHEP_StorageSvc.ppt
File Format: Microsoft Powerpoint - View as HTML
Object Cache. Data **Service**. Manages **object cache**. **Client** Data Access. **Client**.
Client ... Data **Cache**. **Object** type (class **name**); Optional data transform ...
Similar pages

DOPY Users Manual
This brings up the broader issue of what the **naming service** really is. To some extent, the
hub's **registry** is a **naming service**: it maps keys to **object ...**
www.enduden.com/~mmuller/projects/dopy/Manual.html - 21k - Cached - Similar pages

Glossary: WAS v5.1
Process by which an initial reference of the **naming service** is obtained. ..... URL scheme.
A format containing another **object** reference. user **registry ...**
www.skywayradio.com/tech/WAS51/glossary.html - 66k - Cached - Similar pages

Cache SOAP **services** on the **client** side - Java World
SOAP (Simple **Object** Access Protocol) **services** are progressing from lab prototypes to ...
Moreover, we introduce a mechanism for automatic **client-cache ...**
www.javaworld.com/javaworld/jw-03-2002/jw-0308-soap.html - 41k - Jun 16, 2007 -
Cached - Similar pages

The following is a list of changes to the OpenAFS for Window ...
New **registry** value "RxMaxMTU" used to limit the size of the RX packets sent by the AFS
Client Service to the Server. In order to enable OpenAFS to work ...
www.openafs.org/dl/openafs/1.3.61/winnt/afs-changes-since-1.2.txt - 10k -
Cached - Similar pages

Distributed **Name** Servers: **Naming** and **Caching** in Large Distributed

Additional performance benefits result from **client**"s acquiring local caches of **name service**
data treated as hints. A **cache** management strategy that **...**
portal.acm.org/citation.cfm?id=894539&
dl=ACM&coll=portal&CFID=15151515&CFTOKEN=6184618 - Similar pages

Previous 1 **2** 3 4 5 6 7 8 9 1011   **Next**

| naming service register object client. Search |

Search within results | Language Tools | Search Tips

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google